

| Root | Configs | Language files |
|---|--|---|
| How to get Root object. <code>\$root =& XCube_Root::getSingleton();</code> | How to get XOOPS configs. <code>\$root->mContext->getXoopsConfig();</code> | How to get Language Manager object. <code>\$lm =& \$root->mLanguageManager;</code> |
| Current User | How to get a particular site config. <code>\$root->mContext->getXoopsConfig(<i>config_name</i>);</code> | How to include module's main.php. <code>\$lm->loadModuleMessageCatalog(<i>dirname</i>);</code> |
| How to get XoopsUser object. <code>\$user =& \$root->mContext->mXoopsUser;</code> | How to get module configs. <code>\$root->mContext->mModuleConfig;</code> | How to include module's admin.php. <code>\$ml->loadModuleAdminMessageCatalog(<i>dirname</i>);</code> |
| How to get user's id number. <code>\$user->uid();</code> | How to get a particular config in this module. <code>\$root->mContext->mModuleConfig[<i>config_name</i>];</code> | How to include module's modinfo.php. <code>\$ml->loadModinfoMessageCatalog(<i>dirname</i>);</code> |
| How to get user's name. <code>\$user->uname();</code> | How to get specific modules' configs. <code>\$ch=& xoops_gethandler('config');</code> <code>\$mconf = \$ch->getConfigsByDirname(<i>dirname</i>);</code> | Others |
| How to get groups which user belongs. <code>\$user->getGroups();</code> | Modules | How to redirect. <code>\$root->mController->executeRedirect(<i>url</i>, <i>time</i>, <i>msg</i>);</code> |
| How to increment user's posts. <code>\$user->incrementPost();</code> | How to get current module's object. <code>\$mdl =& \$root->mContext->mModule->mXoopsModule;</code> | How to pretend to load Core. <code>define('_LEGACY_PREVENT_LOAD_CORE_', 1);</code> |
| User Roles | How to get current module's directory name. <code>\$mdl->get('dirname');</code> | How to pretend to execute Common. <code>define('_LEGACY_PREVENT_EXEC_COMMON_', 1);</code> |
| How to check what roles user play. <code>\$root->mContext->mUser->isInRole(<i>role_name</i>);</code> | How to get current module's name. <code>\$mdl->get('name');</code> | Constants |
| Name of system roles. Site.GuestUser : Anonymous users. Site.RegisteredUser : Registered users. Site.Administrator : Who can access admin menu Site.Owner : User who has all rights. Module. <i>dirname</i> .Admin : A module's admin Module. <i>dirname</i> .Visitor : A module's visitors | How to get current module's id. <code>\$mdl->get('id');</code> | Path XOOPS_ROOT_PATH XOOPS_CACHE_PATH XOOPS_MODULE_PATH XOOPS_UPLOAD_PATH XOOPS_THEME_PATH XOOPS_COMPILE_PATH |
| Data Base | GET / POST | URL XOOPS_URL XOOPS_MODULE_URL XOOPS_UPLOAD_URL XOOPS_THEME_URL |
| How to get xoopsDB object. <code>\$db =& \$root->mController->mDB;</code> | How to get GET/POST value. <code>\$root->mContext->mRequest->getRequest(<i>name</i>);</code> | Groups XOOPS_GROUP_ADMIN XOOPS_GROUP_USERS XOOPS_GROUP_ANONYMOUS |
| To set prefix to table name. <code>\$db->prefix(<i>table_name</i>);</code> | How to get GET/POST value. <code>xoops_getrequest(<i>name</i>);</code> | |
| To send query. <code>\$db->query(<i>mysql_expression</i>);</code> | Template Tips | |
| To send forcibly query . <code>\$db->queryF(<i>mysql_expression</i>);</code> | How to get user's properties by uid. <{\$uid xoops_user: <i>property_name</i> > | |
| | How to get user's avatar URL by uid. <{\$uid xoops_user_avatarize}> | |
| | How to print date time which adjusted to time-zone. <{\$timeStamp xoops_formattimestamp:!}> | |